

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MATTING AGENT UB-100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Additive, Paint

Recommended restrictions on use : For use in industrial installations or professional treatment only.

1.3 Details of the supplier of the safety data sheet

Company : Roberlo s.a.
Ctra. Nacional II, Km. 706,5
17457 Riudellots de la Selva
Spain

Telephone : +34972478060

Telefax : +34972477394

E-mail address of person responsible for the SDS : msds@roberlo.com

1.4 Emergency telephone number

+34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - repeated exposure, Category 2 H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Hazard pictograms :



Signal word : Warning

Hazard statements :
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P260 Do not breathe spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
xylene (mixture of isomers)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2	Acute Tox. 4; H302 Acute Tox. 4; H312	>= 20 - < 30

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

n-butyl acetate	01-2119475112-47 123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 20
xylene (mixture of isomers)	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	>= 10 - < 20
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336, EUH066 Aquatic Chronic 2; H411	>= 2.5 - < 10
Solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 649-356-00-4	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 1 - < 2.5
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2.5
Substances with a workplace exposure limit :			
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

- If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Headache
Vertigo
Fatigue
Weakness
Skin contact may provoke the following symptoms:
Redness
Pain
Ingestion may provoke the following symptoms:
Abdominal pain
Nausea
Vomiting
Diarrhoea

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

areas and containers place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Storage period : 12 Months

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : For the use of this product do not exist particular recommendations apart from that already indicated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 333 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
silica amorphous	112926-00-8	TWA (inhalable dust)	6 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

			therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used	
		TWA (Respirable dust)	2.4 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
xylene (mixture of isomers)	1330-20-7	TWA	50 ppm 220 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m ³	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 274 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 548 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	100 ppm 441 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	125 ppm 552 mg/m ³	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	133 mg/m ³
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	480 mg/m ³
xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
Low boiling point naphtha - unspecified	Workers	Inhalation	Long-term systemic effects	608 mg/m ³
ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection
Material : Solvent-resistant gloves

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.
Dust safety masks are recommended when the dust concentration is more than 10 mg/m³.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : paste, viscous
- Colour : colourless
- Odour : characteristic
- pH : Not applicable
- Melting point/range : not determined
- Boiling point/boiling range : not determined
- Flash point : 30 °C
Method: ISO 1523, closed cup
Setaflash
- Upper explosion limit / Upper flammability limit : not determined
- Lower explosion limit / Lower flammability limit : not determined
- Vapour pressure : not determined
- Density : 1.06 g/cm³ (20 °C)
Method: ISO 2811-1
- Solubility(ies)
Water solubility : immiscible
- Viscosity
Viscosity, dynamic : 2,250 mPa.s (20 °C)
Method: ISO 2555
- Viscosity, kinematic : > 20.5 mm²/s (40 °C)

9.2 Other information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

2-butoxyethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 1,880 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Method: Converted acute toxicity point estimate

n-butyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 10,768 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 17,600 mg/kg
Method: OECD Test Guideline 402

xylene (mixture of isomers):

Acute oral toxicity : LD50 Oral (Rat): 4,300 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 22.08 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Converted acute toxicity point estimate

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): 8,400 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3400 ppm
Exposure time: 4 h
Test atmosphere: vapour

Solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 Oral (Rat): 3,592 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3,160 mg/kg
Method: OECD Test Guideline 402

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 17.4 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Test atmosphere: gas
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg
Method: OECD Test Guideline 402

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 8,532 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 35.7 mg/l
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): 5,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Result: Skin irritation

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Germ cell mutagenicity-
Assessment : Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Carcinogenicity -
Assessment : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Reproductive toxicity -
Assessment : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-butoxyethyl acetate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Fish): 28 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 37 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : | EC50 (Algae): 1,570 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

n-butyl acetate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Fish): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 32 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Toxicity to algae : EC50 (Algae): 675 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

xylene (mixture of isomers):

Toxicity to fish : LC50 (Fish): 14 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 16 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): > 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Hydrocarbons, C9, aromatics:

Toxicity to fish : LC50 (Fish): 9.22 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 6.14 mg/l
aquatic invertebrates : Exposure time: 48 h

Solvent naphtha (petroleum), light arom.:

Toxicity to fish : LC50 (Fish): 9.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 3.2 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 2.9 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ethylbenzene:

Toxicity to fish : LC50 (Fish): 12 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1.8 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Algae): 33 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

2-methoxy-1-methylethyl acetate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

-
- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Fish): 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 408 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : | EC50 (Algae): 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

SECTION 14: Transport information

14.1 UN number

ADR : 1263
IMDG : UN 1263
IATA (Cargo) : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT
IATA (Cargo) : Paint

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA (Cargo) : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

Remarks : Exemption: Not subject to ADR according to section 2.2.3.1.5, Transport in accordance with 2.3.2.5 of the IMDG Code.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t

Other regulations:

The product is classified and labelled in accordance with EC directives or respective national laws.

15.2 Chemical safety assessment

The supplier has not carried out evaluation of chemical safety.

SECTION 16: Other information

Full text of H-Statements

EUH066	: Repeated exposure may cause skin dryness or cracking.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Chronic aquatic toxicity
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : <http://echa.europa.eu>, <http://eur-lex.europa.eu>

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



MATTING AGENT UB-100

Version
1.1

Revision Date:
04.04.2018

SDS Number:
H52357

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN